




安利消防器材有限公司

Safety Fire Fighting Equipment Ltd.

消防處註冊消防裝置承辦商 • 機電工程署註冊電業承辦商

緊急後備照明燈 (發光二極管) Recess type Emergency Light (LED)



Model No. / 型號	Supalux SLEL-05-A
Housing / 外殼	Powder Coated Mild Steel
Head Lamp / 燈頭	2 x 1W High Quality LED chips
Rechargeable Battery / 充電池	Ni-Cd 3.6V 800mAh (full charged within 12 hrs)
Normal Output / 輸出功率	2W (excess 2 meters more than 2 lux)
Inner features / 燈內裝置	防火線路版及 UL 防火電子線 Fire Resistant P.C. Board & UL Fire Resistant Wire
Outside features / 燈外裝置	紅色充電池指示燈、黃色故障燈、綠色電源指示燈及測試掣 RED LED Charging, Yellow LED Fault, Green LED Main & Test switch
Discharge Duration/可亮時間	Over 2 Hours
Circuit Design / 線路設計	一份低電壓斷路器，以便於充電池耗盡後將電池截斷 A low voltage cut out to disconnect the battery when fully discharged
Testing Report / 測試證書	The HK Polytechnic University #SL-16-T026
Testing Standard / 測試標準	香港消防處牌照及審批總區: [PPA/104(A) 第四次修訂] HKFSD Licensing & Certification Command [PPA/104(A) 4 th Revision]
Line Voltage / 電壓	AC 220 - 240V 50 Hz
Weight / 重量	2.50 kg
Dimension / 燈箱尺寸	360 x 170 x 50mm

All photos are for reference only. 圖片只供參考

All Technical Information is provided by Manufacturer. The Dealer is not held responsible for any inaccuracies in the data.