安利消防器材有限公司
Safety Fire Fighting Equipment Ltd.
消防處註冊消防裝置承辦商 • 機電工程署註冊電業承辦商
www.FIRE.hk safety@fire.hk 香港灣仔吉安街4號地下 G/F, No. 4 Kat On Street, Wan Chai, HK 2866 6895 2866 6795

Supalux Emergency LED Exit Sign Box

Directional Sign:

Model	Supalux CS	Supalux CS/G
Lamp	12 Pieces High intensity Green LEDs	12 Pieces High intensity White LEDs
Housing	Aluminum alloy materials	
LED Operating Life	Approx. 100,000 hrs	
Rechargeable Battery	NiCd 4.8V 800mAh	
Recharge Period	≤10 Hours	
Rated Power	≤3.8W	
Operating Temp.	0ºC to 50ºC	
Outside Features	"Green" power indication light & "Test" switch	
Charge Indicator	Green LED	
Test Button	Press type	
Discharge Duration	≥ 2 Hours	
System Mode	Maintained Type	
Testing Standard	HKFSD Fire Protection Command: FSD code of practice circular letter No. 2/2000 (12 April 2000) Clause 5.10 Exit Signs BS5266: Part 1	
Input Voltage	AC 180V–242V, 50Hz	
Weight	Case Box : 0.90kgs Plate : 0.85kgs Total Weight : 1.75kgs	
Dimensions (L x H x D) mm	Case Box : 404 x 83 x 44mm Plate : 400 x 180 x 10mm Plate (visible part) : 400 x 165 x 10mm Overall (visible part) : 404 x 248 x 44mm	
Signage Panel	EXIT 出口 or Directional	
Style	Single Side or Double Sides	

出口指示燈牌由鋁質外殼及亞加力膠片組合而成，膠片由超光及優質的綠色 LED 燈作光源，使膠片上蝕刻字樣及圖案更清晰易讀。LED 燈泡省電及長壽，極符合經濟效益。**三年特長保養期**。

All photos are for reference only. 圖片只供參考

All Technical Information is provided by Manufacturer. The Dealer is not held responsible for any inaccuracies in the data.