



安利消防器材有限公司

Safety Fire Fighting Equipment Ltd.

消防處註冊消防裝置承辦商 • 機電工程署註冊電業承辦商




www.FIRE.hk safety@fire.hk

香港灣仔石水渠街90號地下
G/F., No. 90 Stone Nullah Lane, Wan Chai, HK

2866 6895 2866 6795

Supalux

Emergency LED Exit Sign Box

	 <p style="text-align: right;">Directional Sign:</p> 
Model	<p style="text-align: center;">Supalux CS Supalux CS/G</p>
Lamp	<p>12 Pieces High intensity Green LEDs 12 Pieces High intensity White LEDs</p>
Housing	<p style="text-align: center;">Aluminum alloy materials</p>
LED Operating Life	<p style="text-align: center;">Approx. 100,000 hrs</p>
Rechargeable Battery	<p style="text-align: center;">NiCd 4.8V 800mAh</p>
Recharge Period	<p style="text-align: center;">≤10 Hours</p>
Rated Power	<p style="text-align: center;">≤3.8W</p>
Operating Temp.	<p style="text-align: center;">0°C to 50°C</p>
Outside Features	<p style="text-align: center;">"Green" power indication light & "Test" switch</p>
Charge Indicator	<p style="text-align: center;">Green LED</p>
Test Button	<p style="text-align: center;">Press type</p>
Discharge Duration	<p style="text-align: center;">≥ 2 Hours</p>
System Mode	<p style="text-align: center;">Maintained Type</p>
Testing Standard	<p style="text-align: center;">HKFSD Fire Protection Command: FSD code of practice circular letter No. 2/2000 (12 April 2000) Clause 5.10 Exit Signs BS5266: Part 1</p>
Input Voltage	<p style="text-align: center;">AC 180V–242V, 50Hz</p>
Weight	<p style="text-align: center;">Case Box : 0.90kgs Plate : 0.85kgs Total Weight : 1.75kgs</p>
Dimensions (L x H x D) mm	<p style="text-align: center;">Case Box : 404 x 83 x 44mm Plate : 400 x 180 x 10mm Plate (visible part) : 400 x 165 x 10mm Overall (visible part) : 404 x 248 x 44mm</p>
Signage Panel	<p style="text-align: center;">EXIT 出口 or Directional</p>
Style	<p style="text-align: center;">Single Side or Double Sides</p>

出口指示燈牌由鋁質外殼及亞加力膠片組合而成，膠片由超光及優質的綠色 LED 燈作光源，使膠片上蝕刻字樣及圖案更清晰易讀。LED 燈泡省電及長壽，極符合經濟效益。三年特長保養期。

All photos are for reference only. 圖片只供參考

All Technical Information is provided by Manufacturer. The Dealer is not held responsible for any inaccuracies in the data.