






安利消防器材有限公司 Safety Fire Fighting Equipment Ltd.

消防處註冊消防裝置承辦商 • 機電工程署註冊電業承辦商

Supalux Emergency LED Exit Sign Box

	 <p style="text-align: right;">Directional Sign:</p> 
Model	Supalux CS
Housing	Aluminum alloy materials
Lamp	5mm Green Super-bright LED line
LED Operating Life	Approx. 100,000 hrs
Rechargeable Battery	NiCd 4.8V 800mAh
Recharge Period	≤10 Hours
Rated Power	≤3.8W
Operating Temp.	0°C to 50°C
Outside Features	"Green" power indication light & "Test" switch
Charge Indicator	Green LED
Test Button	Press type
Discharge Duration	≥ 3 Hours
System Mode	Maintained Type
Testing Standard	HKFSD Fire Protection Command: FSD code of practice circular letter No. 2/2000 (12 April 2000) Clause 5.10 Exit Signs BS5266: Part 1
Input Voltage	AC 180V–242V, 50Hz
Weight	Case Box : 0.90kgs Plate : 0.85kgs Total Weight : 1.75kgs
Dimensions (L x H x D) mm	Case Box : 404 x 83 x 44mm Plate : 400 x 180 x 10mm Plate (visible part) : 400 x 165 x 10mm Overall (visible part) : 404 x 248 x 44mm
Signage Panel	EXIT 出口 or Directional
Style	Single Side or Double Sides

出口指示燈牌由鋁質外殼及亞加力膠片組合而成，膠片由超光及優質的綠色 LED 燈作光源，使膠片上蝕刻字樣及圖案更清晰易讀。LED 燈泡省電及長壽，極符合經濟效益。三年特長保養期。

All photos are for reference only. 圖片只供參考

All Technical Information is provided by Manufacturer. The Dealer is not held responsible for any inaccuracies in the data.

香港灣仔麥加力歌街 1-19 號地下 C1 舖 website: www.FIRE.hk email: safety@fire.hk
Shop C1, G/F, 1-19 McGregor Street, Wan Chai, Hong Kong Tel: 2866 6895 Fax: 2866 6795