



# 安利消防器材有限公司 Safety Fire Fighting Equipment Ltd.

消防處註冊消防裝置承辦商 • 機電工程署註冊電業承辦商

## Supalux Emergency LED Exit Sign Box

<b>Model</b>	<b>Supalux DS/W</b>
<b>Housing</b>	Aluminum alloy materials
<b>Lamp</b>	5mm White Super-bright LED line
<b>LED Operating Life</b>	Approx. 100,000 hrs
<b>Rechargeable Battery</b>	NiCd 4.8V 800mAh
<b>Recharge Period</b>	≤10 Hours
<b>Rated Power</b>	≤3.8W
<b>Operating Temp.</b>	0°C to 50°C
<b>Outside Features</b>	"Green" power indication light & "Test" switch
<b>Charge Indicator</b>	Green LED
<b>Test Button</b>	Press type
<b>Discharge Duration</b>	≥ 3 Hours
<b>System Mode</b>	Maintained Type
<b>Testing Standard</b>	HKFSD Fire Protection Command: FSD code of practice Clause 5.10 Exit Signs BS5499: Part 3:1900 & BS5266: Part 1: 1999
<b>Input Voltage</b>	AC 180V–242V, 50Hz
<b>Weight</b>	Case Box : 0.90kgs ; Plate : 0.85kgs Total Weight : 1.75kgs
<b>Dimensions (L x H x D) mm</b>	Case Box : 404 x 83 x 44mm Plate : 400 x 180 x 10mm Plate (visible part) : 400 x 165 x 10mm Overall (visible part) : 404 x 248 x 44mm
<b>Signage Panel</b>	EXIT 出口 or Directional
<b>Style</b>	Single Side or Double Sides

出口指示燈牌由鋁質外殼及亞加力膠片組合而成，膠片由超光及優質的綠色 LED 燈作光源，使膠片上蝕刻字樣及圖案更清晰易讀。LED 燈泡省電及長壽，極符合經濟效益。三年特長保養期。

All photos are for reference only. 圖片只供參考

All Technical Information is provided by Manufacturer. The Dealer is not held responsible for any inaccuracies in the data.

香港灣仔麥加力歌街 1-19 號地下 C1 舖 website: [www.FIRE.hk](http://www.FIRE.hk) email: [safety@fire.hk](mailto:safety@fire.hk)

Shop C1, G/F, 1-19 McGregor Street, Wan Chai, Hong Kong Tel: 2866 6895 Fax: 2866 6795